

DA7.2



Rated Power (20Hz-20KHz, <0.1%THD)	2×750W@8Ωstereo 2×1200W@4Ωstereo 2×1700W@2Ωstereo 2400W@8Ωbridge 3400W@4Ωbridge
A-Guard Protection System	DC protection / Short circuit protection / Smart overheat management / Overheat protection / Input overload protection / Output overload protection / Soft startup protection / Limiter protection Up to 9V
Frequency Response (1W 8Ω stereo)	20Hz-20KHz(±0.3dB)
Sensitivity	0.775V / 36dB / 32dB
Input Connectors Output Connectors	NEUTRIK® male XLR & female XLR 3×NEUTRIK® Speakon NL 4MP
Filter Capacitor Capacity	12000µf / 80V×8
Input Impedance	Balanced 20KΩ / Unbalanced 10KΩ
Crosstalk (20Hz-20KHz, Rated power 8Ω)	≥65dB
S/N Ratio (Rated power 8Ω, A weighted)	≥108dB
Damping Factor (1KHz&8Ω)	≥1000
Intermodulation Distortion (20Hz-20KHz, half power)	≤0.02%
Total Harmonic Distortion (20Hz-20KHz, rated power 8Ω)	≤0.02%
Phase Response (1W&8Ω, 20Hz-20KHz)	20Hz+4° 20KHz-8°
Slew Rate	≥60V/µs
Output Circuitry	Class H ⁺
Power Consumption (Dual channel driven 4Ω, 1/ 8RMS / 230V)	3.4A
Rack Space	2U
Cooling	Back to front venting, mandatory cooling
Dimension (W×H×D)	483×88×456mm
Net Weight	25.0Kg



DA12.2



Rated Power (20Hz-20KHz, <0.1%THD)	2×1200W@8Ωstereo 2×1800W@4Ωstereo 2×2500W@2Ωstereo 3600W@8Ωbridge 5400W@4Ωbridge
A-Guard Protection System	DC protection / Short circuit protection / Smart overheat management / Overheat protection / Input overload protection / Output overload protection / Soft startup protection / Limiter protection Up to 9V
Frequency Response (1W 8Ω stereo)	20Hz-20KHz(±0.3dB)
Sensitivity	0.775V / 36dB / 32dB
Input Connectors Output Connectors	NEUTRIK® male XLR & female XLR 3×NEUTRIK® Speakon NL 4MP
Filter Capacitor Capacity	15000µf / 100V×12
Input Impedance	Balanced 20KΩ / Unbalanced 10KΩ
Crosstalk (20Hz-20KHz, Rated power 8Ω)	≥72dB
S/N Ratio (Rated power 8Ω,A weighted)	≥110dB
Damping Factor (1KHz&8Ω)	≥2000
Intermodulation Distortion (20Hz-20KHz, half power)	≤0.02%
Total Harmonic Distortion (20Hz-20KHz, rated power 8Ω)	≤0.02%
Phase Response (1W&8Ω, 20Hz-20KHz)	20Hz+4° 20KHz-8°
Slew Rate	≥60V/µs
Output Circuitry	Class H ⁺
Power Consumption (Dual channel driven 4Ω, 1/ 8RMS / 230V)	5.3A
Rack Space	3U
Cooling	Back to front venting, mandatory cooling
Dimension (W×H×D)	483×132×506mm
Net Weight	39.0Kg

