

PF8+ MKII

PF8+MKII is a passive crossover full range speaker widely used in fixed installation such as multi-functional hall, museum, house of worship, commercial announcements, etc.


PF8+ MKII adopts customized HF driver with 1.75" voice coil, composite membrane and unique driver protection circuit, and customized 8"LF driver with 2"voice coil. The drivers are with advanced cooling system.


HF horn is made of DMF composite material to ensure very warm and dynamic sound. The coverage angle is (H°×V°) 80°×70° and the horn is 90° rotatable. This ensures accurate coverage no matter in vertical or horizontal direction.

15 years experienced Smart crossover technology, American Benelec XPP audio capacitor, iron-core inductor, customized metal resistor and manually soldered fiber board ensure stability and consistency and zero consumption, even with very high dynamic sound pressure.

The cabinet is made of CNC made Russian birch plywood, and is tongue and groove assembly.







Dimension(W×H×D):256×424×274mm

FEATURES

- Customized driver
- American Benelec XPP audio capacitor with stable quality, reliable performance
- Manually soldered fiber board to ensure zero consumption even in very high dynamic
- Unique driver protection circuit and high-efficient cooling system of
- DMF composite material HF horn design, coverage angle 90° rotatable
- Solid CNC cabinet made of original Russian birch plywood, exquisite outlook and waterproof enclosure
- Tongue and groove assembly, compact and seamless CNC cabinet design ensures low resonance















SYSTEM CONFIGURATION

- PRO series amplifier
- EA5 series subwoofer

SPECIFICATION

Frequency Response (-6dB anechoic chamber)

Rated Power (AES)

Maximum Calculated SPL/1M(Continuous/Peak)

Horizontal Coverage Angle (Symmetrical) Vertical Coverage Angle (Symmetrical)

LF Driver

HF Driver

Crossover Point Impedance

1 Way Amplifier **Hanging Hardwares**

Pole Mount Input Connectors Cabinet Material

Cabinet Color

Dimension (W×H×D)

Net Weight

Passive crossover full range speaker 60Hz-20KHz

200W

118dB/124dB

80°

70°

Customized driver, 2"voice coil,

200W(AES)

Customized driver, 1"exit, 1,75"voice coil, 50W(AES)

2000Hz 8Ω(+1, -1)

2pcs maximum, 4Ω M8 screw

Base hole ф35mm 2×Speaker connector Russian birch plywood CNC made

Black is standard and default color. Consult with Audiocenter sales team

for other customized colors

256×424×274mm

11.5Kg

ACCESSORIES



M8 eyebolt Bearing 200KG



M8 safety bracket Bearing 130KG








Single point hanging frame (PF8*MKII & PF10*MKII90/PF10*MKII60 & PF12*MKII90/PF12*MKII60) Bearing 80KG



Wall mounting frame(PF8*MKII) Bearing 40KG



Flexible wall mounting frame (PF8*MKII & PF10*MKII90/PF10*MKII60 & PF12*MKII90/PF12*MKII60) Bearing 40KG



Horizontal U bracket (PF10*MKII90/PF10*MKII60 & PF12*MKII90/PF12*MKII60 & PF15*MKII90/PF15*MKII60) Bearing 60KG




Coupling bar Bearing 50KG



Three-feet stand Bearing 80KG



Flightcase(customized) For 2 cabinets, with 100mm wheels



Rain bag(customized)

INSTALLATIONS

