


MA12⁺







Dimension(W×H×D):381×582×343mm

SPECIFICATION

Frequency Response(-10dB) 50Hz-20kHz Horizontal Coverage 90° **Vertical Coverage** 60° **Maximum Calculated** 125dB/131dB

SPL/1M(Continuous/Peak)

Customized driver, 1.75" voice coil,

LF Driver Customized 12" driver, 2.5" voice coil

DSP

HF Driver

Processor 48kHz signal sampling frequency MUSIC, FLAT, SPEECH, W/SUB **Presets**

AMPLIFIER Amplifier Circuitry

Class D Power (RMS standards) 800W **Peak Power** 1600W

20Hz-20kHz(±0.5dB) Frequency Response

(1W 8Ω 2ch)

Signal Input

<0.05% Intermodulation Distortion **Total Harmonic Distortion** < 0.05%

Cooling System

Cooling with fans,air convection DC protection, short circuit protection, **Protection** overheat protection, input overload

protection, output overload protection, soft startup protection, overvoltage protection, undervoltage protection Female XLR(Mono jack 6.35),

3.5mm Jack Input, Wireless bluetooth Signal Output Male XLR mixed output or balanced output

Power Input IEC power connector

AC Power Operating Range 100-240V~ (±10%,50/60Hz) 55W Power consumption

(1/8 output power)

CABINET

Cabinet New polypropylene composite material

Cabinet Color Black is the default color

Grille Iron mesh Handles 1 side,1 top

Symmetrical 45° monitor angle Monitor Angle

Hanging Hardwares M8 screw Base hole Φ35mm Pole Mount

Speaker Dimension (W×H×D) 381x582x343mm 426x665x401mm Carton Dimensions (W×H×D)

Net Weight 16.0kg Shipping Weight 19.0ka

PRODUCT PROFILE

The MA12⁺ is crafted from a newly developed polypropylene composite material, custom-molded to deliver a stylish appearance, superior performance, and lightweight usability. Integrated with BrainCore™ technology, the MA12+ achieves high integration of the input signal, power amplifier, and DSP module. This optimizes audio energy for maximum efficiency, ensuring the product is both stable and reliable.

Equipped with Bluetooth and TWS (True Wireless Stereo) technology, the MA12+ enables convenient stereo wireless pairing, allowing users to enjoy stable, high - quality sound anytime, anywhere.

The MA12⁺ can be mounted on a tripod or suspended for use as a main PA speaker and is also suitable for stage monitoring.

SUGGESTED APPLICATION











Lecture Halls

Meeting rooms

worship

Houses of

Museums

Stage Monitor

Weddings

INSTALLATIONS

