T115S-DSP

T115S-DSP is single 15" active DSP- controlled subwoofer with front loaded cabinet design and customized SMPS class D amplifier with built in DSP. With the powerful and dynamic performance, T115S-DSP is a good match for T45-DSP.

3 presets are available for T115S-DSP.

Normal - to match with T45-DSP

Cardioid F - cardioid usage, for front coverage

Cardioid B - cardioid usage, for back coverage

You need to combine Cardioid F and Cardioid B together for cardioid usage.





Dimension(WxHxD):438x600x570mm

FEATURES

- Maximum SPL 136 dB
- Customized driver
- Built in DSP with 96kHz signal sampling frequency, 56bit precision Class D amplifier
- Advanced cooling system in the driver
- Optimized, compact and light weight cabinet design for easy usage
- Durable Polyurea Coating
- Comprehensive accessories for different applications















SYSTEM CONFIGURATION

■ T45-DSP line array

SPECIFICATION

Frequency Response(-10dB) 35Hz-250Hz Maximum Calculated 130dB/136dB

SPL/1M(Continuous/Peak)

DSP

Processor Presets **AMPLIFIER**

Amplifier Circuitry

Power(RMS standards) Peak Power Frequency Response

(1W 8Ω 2ch) Intermodulation Distortion

Total Harmonic Distortion

Protection

< 0.05% Cooling System Cooling with fans, air convection

DC protection, short circuit protection, overheat protection, input overload protection, output overload protection, soft startup protection, overvoltage protection, undervoltage protection

Customized 15" driver, 4"voice coil

96kHz signal sampling frequency Normal.Cardioid F.Cardioid B

Female XLR Signal Input Signal Output Male XLR Power Input Power connector Power Output Power connector

AC Power Operating Range Power consumption

(1/8 output power)

CABINET Cabinet Material Coating

Cabinet Color Grille Handles

Speaker Dimension(WxHxD) Carton Dimensions (WxHxD) Net Weight

Shipping Weight

Pole Mount

100V-130V~ or 220V-240V~(±10%,50/60Hz)

132W

Class D

1000W

2000W

< 0.05%

20Hz-20kHz(±0.5dB)

CNC made of excellent wood **Durable Polyurea Coating** Black is the default color. Contact Audiocenter for customization

Iron mesh 2 side M20 base φ35mm

438x600x570mm 522x695x653mm 43.0kg

46.5kg

03/04




ACCESSORIES



M20 D shackle Bearing 3T



2M / 3M flying belt Made of synthetic fibre, bearing 2T/4T




Frame for flying and ground stacking




Bracket




Coupling bar



Flightcase For 2 cabinets, with 100mm wheels



Dolly



Rain bag(customized)

INSTALLATIONS

