

Butterfly 4ca


Butterfly 4ca consists of 1 pc 4-inch LF driver and 2 pcs soft dome tweeters. The HF have an exclusive T-EYE™ design, and the array layout is assembled in the center front of the speaker. The speaker has a wider frequency response and large near-field coverage, and the sound is especially defined and delicate.

Butterfly 4ca also have a modular design concept, which can be used individually or in combination with multiple speakers. It has good scalability and can flexibly adapt to various environments and applications.

Butterfly 4ca is available both in High Impedance (70V/100V) and Low Impedance (16Ω).

70V: 2.5W/5W/10W/20W

100V: 5W/10W/20W/x



Dimensions(W×H×D): 215×122×165mm

FEATURES

- Waterproof Rating IP54
- Customized ProDriver
- Smart Crossover Design
- Durable ABS cabinet structure
- High Z and Low Z
- Unique Driver Protection Circuit
- T-EYE™ Treble Design
- Extremely Simple Installation
- Flexible and Multiple Applications

ACCESSORIES



• **WM-BTF**
Wall Mount /
Monitor Bracket

• Dimension (W×H×D):
140x55x117mm



• **FF-BTF**
Hanging Frame

• Dimension (W×H×D):
164x100x300mm



• **LAW-BTF**
Wall Mount Bracket

• Dimension (W×H×D):
164x100x300mm



• **PMA-BTF**
Pole Mount Bracket

• Dimension (W×H×D):
164x92x205mm

SPECIFICATION

Type	Point Source / Line Array Loudspeakers
Power (RMS)	60W
Power (CV)	2.5W/5W/10W/20W(70V) 5W/10W/20W (100V)
Frequency Response(-10dB)	100Hz-20kHz
Horizontal Coverage	100°
Vertical Coverage	20°
Maximum Calculated SPL/1M (Continuous/Peak)	111dB/117dB
HF Drive	2x1" Driver
LF Drive	4" Driver
Rated Impedance	16Ω
Crossover Mode	Passive Crossover
Input Connectors	Speakon 4Pin
Cabinet	
Cabinet Material	ABS plastic material
Adjusted Angles	0°,4°
Cabinet Color	Metal gray
Grille	Aluminum mesh
Grille Color	Can be customized
Pole Mount	M10
Support Hole	M10 Support Hole
Speaker Dimension(W×H×D)	215×122×165mm
Carton Dimension(W×H×D)	253×160x247mm
Net Weight	2.5kg
Shipping Weight	2.9kg