


Butterfly 4pro

Butterfly 4pro consists of 1 pc 4-inch LF driver and 2 pcs soft dome tweeters. The HF have an exclusive T-EYETM design, and the array layout is assembled in the center front of the speaker. The speaker has a wider frequency response and large near-field coverage, and the sound is especially defined and delicate.

Butterfly 4pro also have a modular design concept, which can be used individually or in combination with multiple speakers. It has good scalability and can flexibly adapt to various environments and applications.

















Dimensions(W×H×D):215×122×165mm

FEATURES

- Customized ProDriver
- Smart Crossover Design
- Durable ABS cabinet structure
- Unique Driver Protection Circuit
- T-EYETM Treble Design
- Extremely Simple Installation
- Flexible and Multiple Applications

ACCESSORIES



WM-BTF
 Wall Mount /
 Monitor Bracket

Dimension(WxHxD): 140x55x117mm



- FF-BTF Hanging Frame
- Dimension (WxHxD): 164x100x300mm



LAW-BTF
 Wall Mount Bracket





- PMA-BTF Pole Mount Bracket
- Dimension (WxHxD): 164x92x205mm

SPECIFICATION

Type Point Source / Line Array Loudspeakers

Power (RMS) 60W

Power (CV)

Frequency Response(-10dB) 100Hz-20kHz

Horizontal Coverage 100° Vertical Coverage 20°

MaximumCalculatedSPL/1M 111dB/117dB

(Continuous/Peak)

HF Drive 2x1" Driver LF Drive 4" Driver Rated Impedance 16Ω

Crossover Mode Passive Crossover Input Connectors Speakon 4Pin

Cabinet

Cabinet Material ABS plastic material

Adjusted Angles 0°,4°
Cabinet Color Metal gray
Grille Aluminum mesh
Grille Color Can be customized

Pole Mount M10

Support Hole M10 Support Hole
Speaker Dimension(W×H×D) 215×122×165mm
Carton Dimension(W×H×D) 253×160×247mm

Net Weight 2.3kg Shipping Weight 2.7kg