


DS10

DS10 is a point-source loudspeaker with a passive crossover. Housed in a high-grade multi-ply birch enclosure, its symmetrical, compact design delivers true multi-purpose flexibility. A bottom-mounted rigging insert offers selectable 0° or 10° angles, allowing the cabinet to be flown, wall-mounted, or pole-mounted with equal ease-seamlessly adapting to any sound reinforcement scenario.



















Dimension(W×H×D):288x526x325mm

FEATURES

- Waterproof Rating IP54
- Customized ProDriver
- DMF Composite Material Horn Design
- Smart Crossover Design
- Rotatable Horn
- Unique Driver Protection Circuit
- Durable Polyurea Coating

ACCESSORIES



- WM-DS Horizontal U bracket
- Dimension (WxHxD): 539x70x258mm



COV-08 Rain Cover

SPECIFICATION

Type Passive full range loudspeaker Rated power(AES) 250W

55Hz-20kHz Frequency Response(-10dB) Horizontal Coverage 90°/60° Vertical Coverage 60°/90° Max SPL(Continuous/Peak) 124dB/130dB

HF 1.75" voice coil, 1.0" exit LF 10" driver, 2.5" voice coil Impedance 8Ω

Crossover Mode Passive **Crossover Point** 1.4kHz Speakon 4Pin Input Connectors **CABINET**

Cabinet Material CNC machined plywood Coating **Durable Polyurea Coating** Cabinet Color Black is the default color. Grille

Iron mesh Handles 1 back Monitor Angle

Hanging Hardwares M8 screw Pole Mount

Base hole Φ35mm, 0° or 10° options Speaker Dimension (W×H×D) 288x526x325mm 383x610x415mm Carton Dimension (W×H×D)

Net Weight 13.0kg Shipping Weight 16.0kg