



## **DS15**

DS15 is a point-source loudspeaker with a passive crossover. Housed in a high-grade multi-ply birch enclosure, its symmetrical, compact design delivers true multi-purpose flexibility. A bottom-mounted rigging insert offers selectable 0° or 10° angles, allowing the cabinet to be flown, wall-mounted, or pole-mounted with equal ease—seamlessly adapting to any sound reinforcement scenario.









Dimension(W×H×D):421x696x416mm

## **FEATURES**

- Waterproof Rating IP54
- Customized ProDriver
- DMF Composite Material Horn Design
- Smart Crossover Design
- Rotatable Horn
- Unique Driver Protection Circuit
- Durable Polyurea Coating

## **ACCESSORIES**



- WM-DS
   Horizontal U bracket
- Dimension (WxHxD): 710x82x345mm



COV-08
 Rain Cover

## **SPECIFICATION**

Type Passive full range loudspeaker

 Rated power(AES)
 400W

 Frequency Response(-10dB)
 40Hz-20kHz

 Horizontal Coverage
 90°/60°

 Vertical Coverage
 60°/90°

 Max SPL(Continuous/Peak)
 130dB/136dB

HF 1.75" voice coil, 1.0" exit LF 15" driver, 3.0" voice coil

 $\begin{array}{lll} \text{Impedance} & 8\Omega \\ \text{Crossover Mode} & \text{Passive} \\ \text{Crossover Point} & 1.2\text{kHz} \\ \text{Input Connectors} & \text{Speakon 4Pin} \end{array}$ 

CABINET
Cabinet Material
Coating
Coating
Cabinet Color
Grille
CNC machined plywood
Durable Polyurea Coating
Black is the default color.
Iron mesh

Handles 2 side

Monitor Angle Symmetrical 45° monitoring Angle

Hanging Hardwares M8 screw

Pole Mount

Base hole Φ35mm,
0° or 10° options
Speaker Dimension (W×H×D)

Carton Dimension (W×H×D)

516x785x516mm

Net Weight 22.0kg Shipping Weight 26.0kg