


DSL45

DSL45 passive line array adopts front bass reflex design and elaborate driver layout, the cabinet is very small and lightweight. With innovative ETE™ wave guide technology, DSL45 delivers supreme sound performance that no need too much correction while tuning. DSL45 is very compact, but with very high SPL and long throw.

DSL45 is highly integrated. It is a plug and play system with user-friendly ergonomic design accessories to ensure easy and quick installation. The angle of the fly bar can be adjusted 0.5°, 1.5°, 3°, 5°, 7°, 10° according to different venues.



















Dimension(W×H×D):458x293x381mm

FEATURES

- Waterproof Rating IP54
- 127dB Maximum Sound Pressure Level (SPL)
- Customized driver
- The innovative ETE™ waveguide technology can ensure excellent frequency response, to achieve very smooth transitions between HF and LF, which provides precise horizontal coverage and ensures clear and balanced sound for the system.
- Optimized, compact and light weight cabinet design for easy usage
- Durable Polyurea Coating
- Comprehensive accessories for different applications

SPECIFICATION

Type Passive Line Array Loudspeakers

Power 250W Frequency Response(-10dB) 63Hz-20kHz Horizontal Coverage 120°

Vertical Coverage Splay angle dependent

Maximum Calculated 121dB/127dB

SPL/1M(Continuous/Peak)

HF Driver 2x1.0" voice coil and 1.0"exit LF Driver 4x5" driver, 1.0" voice coil

Impedance 8Ω

Crossover Mode Built-in (passive) crossover

Crossover point 1.2kHz Input Connectors Speakon 4Pin

Cabinet

Cabinet Material CNC made of excellent wood Angle Adjustment 0.5°,1.5°,3°,5°,7°,10° Coating **Durable Polyurea Coating** Cabinet Color Black is the default color. Contact Audiocenter for customization

Grille Iron mesh Handles 2 side

Speaker Dimension(W×H×D) 458×293×381mm Carton Dimensions (W×H×D) 389×553×476mm

Net Weight 17.0kg Shipping Weight 20.0kg

ACCESSORIES











PMA-DSL stand



COV-DSL45 Rain Cover

Dimension (WxHxD): 265x102x150mm