

T43


T43 passive Hi Z and Low Z linear source column speaker is built with 4 pcs 3" neodymium drivers. The drivers are arranged by elaborate calculation and PhycalTM physical calibration technology, which makes T43 with wider near-field horizontal and vertical coverage than the normal column speaker, to meet various demands.

T43 is equipped with wall mount brackets to adjust the angle horizontally and vertically. T43 is built-in with voltage and impedance output switch tap, which makes T43 with more applications.









Dimension(W×H×D): 121x549x146mm

FEATURES

- Waterproof Rating IP54
- Customized ProDriver
- Unique Driver Protection Circuit
- Durable Polyurea Coating

SPECIFICATION

Type Hi Z and Low Z Linear Source

Column Speaker

Power 120W 70V/100V Power 70V:6

70V/100V Power 70V:60W/30W/15W/7.5W 100V:60W/30W/15W

Frequency Response 110Hz-20kHz

Horizontal Coverage 120°

Vertical Coverage 40°

MaximumCalculatedSPL/1M 121dB/127dB

(Continuous/Peak)

HF Drive

LF Drive 4x3" Full frequency

Rated Impedance 8Ω

Crossover Mode /
Input Connectors Euroblock

Cabinet

Cabinet Material Wood+Plastic

Coating Durable Polyurea Coating

 Cabinet Color
 Black

 Grille
 Iron mesh

 Speaker Dimension(W×H×D)
 121×549×146mm

 Carton Dimension(W×H×D)
 730×235x210mm

Net Weight 3.6kg
Shipping Weight 9.5kg(2pcs)

ACCESSORIES



 WM05-BL/WM05-W Wall Mount Bracket (vertically installed, able to adjust horizontally and vertically)



• Dimension (WxHxD): 86x85x150mm