


DS06

DS06 is a point-source loudspeaker with a passive crossover. Housed in a high-grade multi-ply birch enclosure, its symmetrical, compact design delivers true multi-purpose flexibility. A bottom-mounted rigging insert allowing the cabinet to be flown, wall-mounted, or pole-mounted with equal ease-seamlessly adapting to any sound reinforcement scenario.



Dimension(W×H×D):200x380x215mm


FEATURES

- Waterproof Rating IP54
- Customized ProDriver
- DMF Composite Material Horn Design
- Smart Crossover Design
- Rotatable Horn
- Unique Driver Protection Circuit
- Durable Polyurea Coating


ACCESSORIES



- WM06-BL/WM06-W
Wall Mount Bracket
- Dimension (WxHxD):
65x130x77mm



- COV-06
Rain Cover



SPECIFICATION

Type	Passive full range loudspeaker
Rated power(AES)	100W
Frequency Response(-10dB)	60Hz-20kHz
Horizontal Coverage	70° /50°
Vertical Coverage	50° /70°
Max SPL(Continuous/Peak)	112dB/118dB
HF	1.0" voice coil, 1.0" exit
LF	6" driver, 1.3" voice coil
Impedance	8Ω(+1,-1)
Crossover Mode	Passive
Crossover Point	1.5kHz
Input Connectors	Speakon 4Pin
CABINET	
Cabinet Material	CNC machined plywood
Coating	Durable Polyurea Coating
Temperature range	-20 C ~+50 C
Cabinet Color	Black is the default color.
Grille	Iron mesh
Handles	/
Monitor Angle	/
Hanging Hardwares	M8 screw
Pole Mount	Base hole Φ35mm
Speaker Dimension (W×H×D)	200x380x215mm
Carton Dimension (W×H×D)	291x471x307mm
Net Weight	8.5kg
Shipping Weight	10.0kg