
Dynamic Audio Solutions


# DS108S

DS108S subwoofers is built from high-density, multi-ply birch plywood. Shaped with CNC-machined, interlocking panels, the cabinets can reduce resonance effectively. Extended low-frequency reach and tightly focused energy deliver deep, punchy bass with exceptional transient response.

IP54






Dimension(W×H×D):400x240x330mm

## FEATURES

- Waterproof Rating IP54
- Customized ProDriver
- Optimized Compact Versatile Enclosure Design for Flexible Use
- Durable Polyurea Coating
- Premium Wood

## SPECIFICATION

| | |
|---|---|
| Type | Passive Subwoofer |
| Power | 200W |
| Frequency Response(-10dB) | 45Hz-200Hz |
| Maximum Calculated SPL/1M(Continuous/Peak) | 115dB/121dB |
| LF Driver | Customized 1x8” Neodymium driver, 2.0”voice coil |
| Impedance | 8Ω(+2,-2) |
| Crossover Mode | External (active) crossover |
| Input Connectors | Speakon 4Pin |
| Cabinet | |
| Cabinet Material | CNC made of excellent wood |
| Coating | Durable Polyurea Coating |
| Temperature range | -20℃~+50℃ |
| Cabinet Color | Black is the default color |
| Grille | Iron mesh |
| Handles | / |
| Base | M20 base Φ35mm |
| Speaker Dimension(W×H×D) | 400×240×330mm |
| Carton Dimensions (W×H×D) | 455×295×390mm |
| Net Weight | 8.0kg |
| Shipping Weight | 10.0kg |