
Dynamic Audio Solutions


DS112S

DS112S subwoofers is built from high-density, multi-ply birch plywood. Shaped with CNC-machined, interlocking panels, the cabinets can reduce resonance effectively. Extended low-frequency reach and tightly focused energy deliver deep, punchy bass with exceptional transient response.

IP54







Dimension(W×H×D):550x340x384mm

FEATURES

- Waterproof Rating IP54
- Customized ProDriver
- Optimized Compact Versatile Enclosure Design for Flexible Use
- Durable Polyurea Coating
- Premium Wood

SPECIFICATION

Type	Passive Subwoofer
Power	400W
Frequency Response(-10dB)	40Hz-200Hz
Maximum Calculated SPL/1M(Continuous/Peak)	121dB/127dB
LF Driver	Customized 1x12”driver, 2.5” voice coil
Impedance	8Ω(+2,-2)
Crossover Mode	External (active) crossover
Input Connectors	Speakon 4Pin
Cabinet	
Cabinet Material	CNC made of excellent wood
Coating	Durable Polyurea Coating
Temperature range	-20℃~+50℃
Cabinet Color	Black is the default color
Grille	Iron mesh
Handles	2 side
Base	M20 base Φ35mm
Speaker Dimension(W×H×D)	550×340×384mm
Carton Dimensions (W×H×D)	605×395×444mm
Net Weight	25.0kg
Shipping Weight	27.0kg