AUDIOCENTER


Dynamic Audio Solutions


DS212S

DS212S subwoofers is built from high-density, multi-ply birch plywood. Shaped with CNC-machined, interlocking panels, the cabinets can reduce resonance effectively. Extended low-frequency reach and tightly focused energy deliver deep, punchy bass with exceptional transient response.

IP54







Dimension(W×H×D):814x378x580mm

FEATURES

- Waterproof Rating IP54
- Customized ProDriver
- Optimized Compact Versatile Enclosure Design for Flexible Use
- Durable Polyurea Coating
- Premium Wood

SPECIFICATION

Type	Passive Subwoofer
Power	800W
Frequency Response(-10dB)	35Hz-150Hz
Maximum Calculated SPL/1M(Continuous/Peak)	127dB/133dB
LF Driver	Customized 2x12” driver, 2.5”voice coil
Impedance	4Ω(+2,-2)
Crossover Mode	External (active) crossover
Input Connectors	Speakon 4Pin
Cabinet	
Cabinet Material	CNC made of excellent wood
Coating	Durable Polyurea Coating
Temperature range	-20℃~+50℃
Cabinet Color	Black is the default color
Grille	Iron mesh
Handles	4 side
Base	M20 base Φ35mm
Speaker Dimension(W×H×D)	814×378×580mm
Carton Dimensions (W×H×D)	458×903×696mm
Net Weight	36.0 kg
Shipping Weight	38.0 kg